

## CHCRUS

This is the accepted manuscript made available via CHORUS. The article has been published as:

## Limits on preserving quantum coherence using multipulse control

Kaveh Khodjasteh, Támas Erdélyi, and Lorenza Viola Phys. Rev. A **83**, 020305 — Published 28 February 2011 DOI: 10.1103/PhysRevA.83.020305

## Limits on Preserving Quantum Coherence using Multi-Pulse Control

Kaveh Khodjasteh,<sup>1</sup> Támas Erdélyi,<sup>2</sup> and Lorenza Viola<sup>1</sup>

<sup>1</sup>Department of Physics and Astronomy, Dartmouth College, 6127 Wilder Laboratory, Hanover, NH 03755, USA

<sup>2</sup>Department of Mathematics, Texas A&M University, College Station, TX 77843, USA

We explore the physical limits of pulsed dynamical decoupling methods for decoherence control as determined by finite timing resources. By focusing on a decohering qubit controlled by arbitrary sequences of  $\pi$ -pulses, we establish a non-perturbative quantitative upper bound to the achievable coherence for specified maximum pulsing rate and noise spectral bandwidth. We introduce numerically optimized control "bandwidth-adapted" sequences that saturate the performance bound, and show how they outperform existing sequences in a realistic excitonic-qubit system where timing constraints are significant. As a byproduct, our analysis reinforces the impossibility of fault-tolerance accuracy thresholds for generic open quantum systems under purely reversible error control.

PACS numbers: 03.67.Pp, 03.67.Lx, 03.65.Yz, 07.05.Dz

Building on the discovery of spin-echo and multiplepulse techniques in nuclear magnetic resonance [1], dynamical decoupling (DD) methods for open quantum systems [2] have become a versatile tool for decoherence control in quantum engineering and fault-tolerant quantum computation. DD involves "open loop" (feedback-free) quantum control based on the application of a timedependent Hamiltonian which, in the simplest setting, effects a pre-determined sequence of unitary operations (pulses) drawn from a basic repertoire. Physically, DD relies on the ability to access control time scales that are short relative to the correlation time scale of the interaction to be removed. The reduction in decoherence is achieved *perturbatively*, by ensuring that sufficiently high orders of the error-inducing Hamiltonian are removed. Recently, a number of increasingly powerful pulsed DD schemes have been proposed and validated in the laboratory. Uhrig DD (UDD) sequences [3], for instance, perturbatively cancel pure dephasing in a single qubit up to an arbitrarily high order n while using a minimal number (n) of pulses, paving the way to further optimization for given sequence duration [4, 5] and/or specific noise environments [6], to nearly-optimal protocols for generic single-qubit decoherence [7]. Experimentally, UDD has been employed to prolong coherence time in systems ranging from trapped ions [4, 5, 8] and atomic ensembles [9] to spin-based devices [10], and to enhance contrast in magnetic resonance imaging of tissue [11].

In a realistic DD setting, the achievable performance is inevitably influenced by errors due to limited control as well as deviations from the intended decoherence model. Since it is conceivable that both model uncertainty and pulse non-idealities can be largely removed by more accurate system identification and control design, some of these limitations may be regarded as non-fundamental in nature. Composite-pulse [12] and pulse-shaping [13] techinques can be used, for instance, to cancel to high accuracy the effects of both systematic control errors and finite-width corrections. We argue, however, that even in a situation where pulses may be assumed perfect and instantaneous, an ultimate constraint is implied by the fact that the rate at which control operations are effected is necessarily finite – as determined by a "minimum switching time"  $\tau_{\rm min}$  for the available control modulation. Our goal in what follows is to rigorously quantify the performance limits to preserving coherence using DD as arising from the sole constraint of *finite timing resources*.

We focus on the paradigmatic case of a single qubit undergoing pure dephasing due to either a quantum bosonic bath at equilibrium or classical (Gaussian) noise, and controlled through a sequence of instantaneous  $\pi$  pulses. While representing an adequate idealization of realistic decoherence control settings [4, 5, 8, 9, 11], this problem is exactly solvable analytically [2, 3], enabling rigorous conclusions to be established. Our first result is a non*perturbative* lower bound for the minimum decoherence error achievable by any DD sequence subject to a timing constraint  $\tau_{\min}$ , for noise spectra characterized by a finite spectral bandwidth  $\omega_c$ . Secondly, we show how to generate "bandwidth-adapted" DD sequences that achieve optimum performance over a desired storage time while respecting the pulse-rate constraint, and demonstrate their advantages in a realistic excitonic qubit. Conceptually, our analysis highlights connections between DD theory and complex analysis of polynomials, and provides further insight into the fundamental capabilities and limitations of open-loop non-dissipative quantum control.

Control setting. — Our target system is a single qubit whose dephasing dynamics in the quantum regime is described by a diagonal spin-boson Hamiltonian of the form  $H = H_S \otimes I_B + H_{SB} + I_S \otimes H_B$ , with  $H_S = \omega S_z$  and

$$H_{SB} = S_z \otimes \sum_k (g_k b_k + g_k^* b_k^\dagger), \quad H_B = \sum_k \omega_k b_k^\dagger b_k.$$

Here,  $I_{S(B)}$  denote the identity operator on the system (bath),  $S_z = \hbar \sigma_z/2$  is the spin operator along the quantization axis, and  $b_k$  ( $b_k^{\dagger}$ ) are canonical ladder operators for the *k*th bosonic mode, characterized by a frequency  $\omega_k$  and coupling strength  $g_k$ . If the bath is initially at thermal equilibrium at temperature  $1/(k_B\beta)$ , its influence on the qubit dynamics is encapsulated by the spectral density function  $I(\omega) \equiv \sum_k |g_k|^2 \delta(\omega - \omega_k)$ . Without loss of generality, we shall assume that  $I(\omega)$  decays to zero beyond a finite ultraviolet cutoff  $\omega_c$ .

DD over an evolution interval [0,T] is achieved by applying a train of n instantaneous  $\pi$  pulses (each implementing a Pauli  $\sigma_x$  operator) at times  $\{t_j\}$ , where  $0 < t_1 < \ldots < t_n < T$ , and we also let  $t_0 \equiv 0$  and  $t_{n+1} \equiv T$ . While keeping the number of pulses n to a minimum may be desirable for various practical reasons, neither n nor the resulting sequence duration need to be constrained a priori. An arbitrary long duration T may, in fact, be needed for quantum memory. In contrast, infinite pulse repetition rates are both fundamentally impossible and undesirable as long as T > 0. Let the minimum switching time  $\tau_{\min} > 0$  lower-bound the smallest control time scale achievable by any sequence:

$$\tau \equiv \min(t_{j+1} - t_j) \ge \tau_{\min}, \quad j \in \{0, \dots, n\}.$$
(1)

If the system is initially in a nontrivial coherent superposition of  $S_z$  eigenstates, its purity in the presence of DD decays with a factor of  $\exp(-2\chi_{\{t_j\}})$ , where the *decoupling error*  $\chi_{\{t_j\}} \geq 0$  can be exactly expressed in the following form (see *e.g.* Eqs. (8c) and (10) in [3]):

$$\chi_{\{t_j\}} = \int_0^\infty \lambda(\omega) |f_{\{\tilde{t}_j\}}(\omega)|^2 d\omega, \quad \tilde{t}_j \equiv \frac{t_j}{\tau}, \quad (2)$$

$$f_{\{\tilde{t}_{j}\}}(\omega) = \sum_{j=0}^{n} (-1)^{j} (e^{i\tilde{t}_{j}\omega\tau} - e^{i\tilde{t}_{j+1}\omega\tau}), \qquad (3)$$

and the "spectral measure"  $\lambda(\omega) \equiv 2 \coth(\beta \omega/2) I(\omega)/\omega^2$ . In terms of the rescaled pulse times  $\tilde{t}_j$ , Eq. (1) becomes  $\tilde{t}_{j+1} - \tilde{t}_j \geq 1$ . Physically, Eqs. (2)-(3) can also describe the purity decay resulting from pure dephasing in the semi-classical limit, as due to stochastic fluctuations of the qubit energy splitting and experimentally investigated in [4, 5, 9]. In this case,  $H_{SB} \equiv 0$  and  $H_S = [\omega + \xi(t)]S_z$ , where  $\xi(t)$  is a Gaussian random variable with a power spectrum  $S(\omega)$  [14]. In order to evaluate  $\chi_{\{t_j\}}$ , it suffices to redefine  $\lambda(\omega) = S(\omega)/2\pi\omega^2$ . The objective of DD is to minimize  $\chi_{\{t_j\}}$ . Our main problem then directly ties to the following: Given the fundamental constraint of Eq. (1), what is a lower bound on  $\chi_{\{t_i\}}$ ?

Non-perturbative performance bound. — A lower bound on  $\chi_{\{t_j\}}$  can be obtained by restricting the integral in Eq. (2) to a finite range  $[0, \omega_c]$ , with a tight bound ensuing if  $\omega_c$  coincides with the spectral cutoff in either  $I(\omega)$ or  $S(\omega)$ . We separate the dependencies of  $\chi_{\{t_j\}}$  upon the timings and the spectral measure  $\lambda(\omega)$  by applying Cauchy's inequality to the functions  $\lambda^{1/2}|f|$  and  $\lambda^{-1/2}$ :

$$\chi_{\{t_j\}} \ge \frac{1}{M_{\{\lambda\}}} \Big( \int_0^{\omega_c} |f_{\{\tilde{t}_j\}}(\omega)| d\omega \Big)^2, \ M_{\{\lambda\}} \equiv \int_0^{\omega_c} \frac{d\omega}{\lambda(\omega)}.$$
(4)

Thus, the integral  $\int_0^{\omega_c} |f_{\{\tilde{t}_j\}}(\omega)| d\omega$ , which is the  $L_1$ -norm of the "filter function"  $f_{\{\tilde{t}_j\}}$  over  $[0, \omega_c]$ , determines a worst-case lower bound on  $\chi_{\{t_j\}}$  for all spectral densities  $\lambda(\omega)$  for which the integral defining  $M_{\{\lambda\}}$  is finite.

Interestingly, upon letting  $e^{i\omega\tau} \equiv z \in \mathbb{C}$  in Eq. (3), the function  $f_{\{\tilde{t}_j\}}(\omega)$  takes the form of a complex "polynomial"  $P_{\{\tilde{t}_i\}}(z)$  with non-integer exponents. Such *Müntz* 

polynomials have been studied in the mathematical literature, and a plethora of results (and conjectures) exist on their associated norm inequalities, zeroes, and multiplicities [15]. The (now resolved) Littlewood conjecture in harmonic analysis [16] may be invoked, in particular, to lower-bound the  $L_1$ -norm of  $f_{\{\tilde{t}_i\}}$ :

$$\chi_{\{t_j\}} \ge \frac{\omega_c^2}{M_{\{\lambda\}}} C(\log n)^2, \quad \text{if } \omega_c \tau > 2\pi, \tag{5}$$

with C = O(1). Also note that, regardless of  $\omega_c \tau$ , an upper bound follows immediately from Eq. (2):  $\chi_{\{t_j\}} \leq m_{\{\lambda\}}n^2$ , where  $m_{\{\lambda\}} \equiv \int_0^\infty \lambda(\omega)d\omega$ . Eq. (5) implies that in the "slow-control" regime where  $\omega_c \tau > 2\pi$ , the DD error worsens when more pulses are applied, and coherence may be best preserved by doing nothing. This reinforces how sufficiently fast modulation time scales are essential for achieving decoherence reduction, as we discuss next.

The "fast-control" regime  $(\omega_c \tau < 2\pi)$  is implicit in perturbative DD treatments, where the filter function  $f_{\{\tilde{t}_j\}}(\omega)$  is chosen to have a Taylor series that starts at  $(\omega\tau)^m$ , so that  $\chi_{\{t_j\}}$  remains small for sufficiently small values of  $\omega_c\tau$ . While this perturbative approach has been used for designing efficient DD schemes, it cannot lead to a lower bound on the attainable DD error in the presence of a timing constraint. Consider for example UDD<sub>n</sub> sequences, in which case  $t_j = T \sin^2[\pi j/(2n+2)]$  for  $j = 1, \dots, n$ , and  $\tau \equiv t_1$ . If  $\tau$  is kept fixed, increasing n is only possible at the expense of lengthening the total duration as  $T(n) = \mathcal{O}[\tau n^2]$ . Irrespective of the fact that perturbatively the error scales as  $\mathcal{O}[(\omega_c\tau)^n]$ , it carries a prefactor that grows too fast with n, eventually causing the perturbative description to break down [17, 18].

A non-perturbative lower bound may be established by directly mapping the  $L_1$ -norm integral of  $f_{\{\tilde{t}_j\}}$  to the size of the corresponding Müntz polynomial  $P_{\{\tilde{t}_j\}}(z)$  over an arc of the unit circle of length  $\omega_c \tau$ . Theorem 2.2 in [19], in conjunction with Eq. (4), then implies:

$$\chi_{\{t_j\}} \ge \frac{1}{M_{\{\lambda\}}\tau^2} c e^{-a/(\omega_c \tau)}, \quad \text{if } \omega_c \tau < 2\pi, \qquad (6)$$

for some numeric constants c and a independent of  $\tau$ ,  $\omega_c$ , and  $\{t_j\}$ . The bound in Eq. (6) is strictly positive for spectral measures of compact support. That it *cannot* be obtained by perturbative methods is manifest from the fact that it describes an essential singularity in  $\omega_c \tau$ .

It is worth to further interpret Eq. (6) in the light of existing results. If the control rate is identified as the key resource that DD leverages for removing errors, a zero lower bound on  $\chi_{\{t_j\}}$  would allow, in principle, arbitrarily high DD accuracy to be achieved by using sufficiently long sequences with a *fixed*  $\tau_{\min}$  – that is, in analogy with fault-tolerant quantum computation [20], with a constant resource overhead relative to the noise-free case. Historically, the impossibility of reliable computation with a constant blow-up in resources (circuit depth) was established in [21] in the broader context of noisy *reversible* 




FIG. 1: (Color online) Decoupling error for  $\text{UDD}_n$  sequences vs.  $\omega_c \tau$ , for a "flat" spectral measure  $\lambda^{[0]}(\omega) \equiv \Theta(\omega - \omega_c)$ . The comparison curve denotes the general lower bound, Eq. (6), evaluated for a = 3, c = 1/2, chosen to approximate a fit.

circuits, both classical and quantum. Therefore, our results may be taken to reinforce the fundamental limitations of purely unitary quantum error correction, while *explicitly* characterizing the way in which such limiting performance depends upon the physical parameters.

Achieving the performance bound.— Note that the minimum switching time  $\tau_{\min}$  enters Eq. (6) naturally, whereas both the total duration T and pulse number n are markedly absent from it. Thus interestingly, *if* the bound can be achieved, it should be possible to do so irrespective of how long T, provided that n is unconstrained. We can show that the error associated with UDD sequences,  $\chi_n^{\text{UDD}}$ , saturates the fundamental limit in Eq. (6) in functional form although *not* necessarily in *absolute* sense (see also Fig. 1). This follows from noting that an upper bound to  $\chi_n^{\text{UDD}}$  in the presence of a hard spectral cutoff may be obtained from an upper bound to  $|f_n^{\text{UDD}}(\omega)|$ , by tailoring n to the bandwidth,  $n \equiv n_0 \approx 1/(e^2\omega_c\tau)$  (see Remark 2.6 in [19]). This yields:

$$\chi_n^{\text{UDD}} \le m_{\{\lambda\}} \cdot \max_{\omega \in [0,\omega_c]} |f_{n_0}^{\text{UDD}}(\omega)|^2 \le \frac{m_{\{\lambda\}}}{\omega_c \tau} c' e^{-a'/(\omega_c \tau)},$$

where  $c' = 2/(\pi e^2)$ ,  $a' = 2/e^2$ , and a similar functional form as in Eq. (6) is manifest. With  $\tau \equiv t_1 \equiv \tau_{\min}$  fixed, the duration T of the "tailored UDD<sub>n</sub>" sequences scales as  $\mathcal{O}[1/(\omega_c^2 \tau_{\min})]$ , and the longest allowed  $\tau$ -value that results in coherence improvement scales as  $1/(n\omega_c)$ . Thus, UDD provides no guarantee that the error reaches its absolute minimum and accessing the required  $\tau$  becomes increasingly harder as T grows. This motivates searching for DD sequences that can operate *beyond* the perturbative regime and retain their efficacy over the broadest range possible, up to  $1/(n\omega_c) \lesssim \tau \lesssim 1/\omega_c$ .

Various optimized DD strategies have been investigated for the qubit-dephasing setting under consideration. In "locally optimized" (LO) DD [4], optimal pulse timings are determined via direct minimization of the error  $\chi_{\{t_j\}}$  for a fixed target storage time T, whereas in "optimized noise filtration" (OF) DD, only the integral of the filter function is minimized [5] (see also [6] for a noiseadapted perturbative approach). While LODD/OFDD




FIG. 2: (Color online) Decoupling error for BADD (dashed), LODD (dotted), and UDD (solid) sequences vs. total duration T with the minimum interval  $\tau$ 's indicated, for a dephasing exciton qubit operating at temperature 77K (see text). The search space for BADD and LODD covers up to n = 100pulses, whereas for UDD  $n \leq 20$ . See [22] for further detail and a comparison between different pulse timing patterns.

can access regimes where perturbative approaches are not efficient, they focus on matching the total sequence duration T as the fundamental constraint. However, this may fail to produce a satisfactory control solution if the timing constraint imposed by Eq. (1) is significant.

To guarantee that such a fundamental limitation is obeyed, we introduce optimized bandwidth-adapted DD (BADD) sequences where *both* the minimum switching time and the total time are constrained from the outset, see Supplementary Material in [22] for additional technical detail. We demonstrate the usefulness of BADD by focusing on the exciton qubit analyzed in [18], for which a spin-boson dephasing model with a supra-Ohmic spectral density and a Gaussian cutoff is appropriate,  $I^{\omega_c,s}(\omega) =$  $\alpha \omega^s \exp(-\omega^2/\omega_c^2)$  with s = 3,  $\alpha \approx 1.14 \times 10^{-26} \mathrm{s}^2$ ,  $\omega_c \approx 3 \,\mathrm{rad\,ps^{-1}}$ , and the need to avoid unwanted excitation of higher-energy levels enforces a timing constraint  $\tau_{\rm min} \approx 0.1$  ps [23]. The results are summarized in Fig. 2. Besides indicating the inadequacy of perturbative UDD for  $T \gtrsim 1$  ps, two main features emerge. First, as predicted by Eq. (6), the minimum error achievable by BADD is mainly dictated by  $\tau$ , largely independently of the total time T. Second, LODD performance is fairly sensitive to the timing constraint: for a fixed T (10 ps in Fig. 2), "softening" the constraint selects LODD sequences that outperform BADD, the opposite behavior being seen if the constraint on the intended  $\tau$  is "hardened". Thus, a BADD protocol effectively optimizes over a set of LODD sequences where the timing constraint is only approximately met, consistent with intuition.

In practice, an important question is whether the performance of a DD scheme is robust against uncertainties in the underlying spectral measure: in particular, sequences adapted to a presumed  $\omega_c \tau_{\min}$  need not be adequate for the actual  $\omega'_c \tau_{\min}$ . Some illustrative results are depicted in Fig. 3 for sequences subject to the same timing constraint, but applied to a setting where  $\omega'_c \neq \omega_c$ . Clearly, a smaller cutoff  $\omega'_c$  leads to smaller decoherence,




FIG. 3: (Color online) Purity loss,  $1 - e^{-2\chi_{\{t_j\}}}$ , vs. actual over presumed cutoff,  $\omega'_c/\omega_c$ , for the supra-Ohmic Gaussian spectral density (s = 3) corresponding to the exciton qubit. All sequences are adapted to  $T \approx 10$  ps,  $\tau \approx 0.1$  ps. Varying the "actual" power law of the noise to s = 4 and s = 2 resulted in a qualitatively similar behavior (data not shown).

but much more so for perturbative UDD sequences. Expectedly, the knowledge of the spectral density explicitly assumed in generating BADD and LODD results in far better coherence compared to OFDD and UDD, especially when this knowledge is precise ( $\omega_c'/\omega_c = 1$ ) or overestimates the cutoff. Comparatively, BADD sequences appear to be more robust than LODD sequences when the cutoff is underestimated.

*Discussion.*— Our mathematical description has relied on the solvability of the dephasing spin-boson model in the limit of instantaneous control pulses, however we expect similar timing-induced lower bounds to exist under more general conditions. In principle, non-Gaussian

- E. L. Hahn, Phys. Rev. 80, 580 (1950); U. Haeberlen and J. S. Waugh, Phys. Rev. 175, 453 (1968).
- [2] L. Viola and S. Lloyd, Phys. Rev. A 58, 2733 (1998); L.
  Viola, E. Knill, and S. Lloyd, Phys. Rev. Lett. 82, 2417 (1999).
- [3] G. S. Uhrig, Phys. Rev. Lett. 98, 100504 (2007).
- [4] M. J. Biercuk *et al.*, Nature **458**, 996 (2009); Phys. Rev. A **79**, 062304 (2009).
- [5] H. Uys, M. J. Biercuk, and J. J. Bollinger, Phys. Rev. Lett. 103, 040501 (2009).
- [6] S. Pasini and G. S. Uhrig, Phys. Rev. A 81, 012309 (2010); Y. Pan, Z. Xi, and W. Cui, arXiv:1001.2960.
- [7] J. R. West, B. H. Fong, and D. A. Lidar, Phys. Rev. Lett. 104, 130501 (2010).
- [8] D. J. Szwer *et al.*, arXiv:1009.6189.
- [9] Y. Sagi, I. Almog, and N. Davidson, Phys. Rev. Lett. 105, 053201 (2010).
- [10] J. Du et al., Nature 461, 1265 (2009).
- [11] E. R. Jenista et al., J. Chem. Phys. 131, 240510 (2009).
- [12] K. R. Brown, A. W. Harrow, and I. L. Chuang, Phys. Rev. A 70, 052318 (2004).
- [13] L. P. Pryadko and G. Quiroz, Phys. Rev. A 77, 012330 (2008); G. S. Uhrig and S. Pasini, New J. Phys. 12, 045001 (2010).

classical dephasing such as random telegraph noise could be addressed based on the exact solution presented in [24], whereas non-bosonic dephasing models of the form  $H_{SB} + H_B \equiv S_z \otimes B_z + B_0$ , could be tackled by matching the leading-order contributions in  $B_z$  with the bosonic case studied here. Note, however, that bounded timing resources do not prevent the DD accuracy bound to be zero in *special* cases – such as "monochromatic" or "non-dynamical" baths  $(H_B = 0)$ , for both of which the length of the arc appearing in Eq. (6) vanishes. Similarly, "nilpotent" environments, where powers of the bath operators in  $H_{SB}$  and  $H_B$  vanish at some order, allow perturbative DD schemes to achieve perfect decoupling, as perturbation theory becomes exact. For more "adversarial" environments, where  $H_{SB}$  is not restricted to but includes single-axis decoherence, similar lower bounds must exist by inclusion. Elucidating the algebraic features responsible for a finite vs. zero performance bound remains an interesting open problem with implications for quantum error correction in general. As opposed to pulsed control scenarios, continuous-time modulation subject to finite energy/bandwidth constraints has also been explored for decoherence control [25]. Although, even for a purely dephasing qubit, finding the optimal modulation requires solving a non-linear integro-differential equation, it would be interesting to quantify the extent to which the extra freedom afforded by continuous controls may improve the achievable performance lower bounds.

We thank Michael Biercuk, Irene D'Amico, Daniel Lidar, and John Preskill for valuable input. Work supported from the NSF through Grant No. PHY-0903727.

- [14] L. Cywiński et al., Phys. Rev. B 77, 174509 (2008).
- [15] P. B. Borwein and T. Erdélyi, *Polynomials and Polynomial Inequalities* (Springer Verlag, Berlin, 1995).
- [16] F. L. Nazarov, St. Petersburg Math. J. 7, 265 (1996).
- [17] G. S. Uhrig and D. A. Lidar, Phys. Rev. A 82, 012301 (2010).
- T. E. Hodgson, L. Viola, and I. D'Amico, Phys. Rev. B 78, 165311 (2008); Phys. Rev. A 81, 062321 (2010).
- [19] T. Erdélyi, K. Khodjasteh, and L. Viola, arXiv:math.CA/1006.4323.
- [20] J. Preskill, Proc. R. Soc. London A 454, 385 (1998).
- [21] D. Aharonov, M. Ben-Or, R. Impagliazzo, and N. Nisan, arXiv:quant-ph/9611028.
- [22] Supplementary Material available at http://link.aps.org/supplemental/????.
- [23] Typical pulse-widths for this system are on the order of  $\tau_p \approx 10$  fs. The analysis in [18] shows that treating pulses as instantaneous is accurate (to within  $\approx 0.01\%$ per pulse) as long as  $\tau_p/\tau_{\rm min} \lesssim 10$ .
- [24] S. Kitajima, M. Ban, and F. Shibata, J. Phys. A 43, 135504 (2010).
- [25] G. Gordon, G. Kurizki, and D. A. Lidar, Phys. Rev. Lett. 101, 010403 (2008).