

CHCRUS

This is the accepted manuscript made available via CHORUS. The article has been published as:

Gyroscopes based on nitrogen-vacancy centers in diamond

M. P. Ledbetter, K. Jensen, R. Fischer, A. Jarmola, and D. Budker
Phys. Rev. A 86, 052116 — Published 19 November 2012
DOI: 10.1103/PhysRevA.86.052116

Gyroscopes based on nitrogen-vacancy centers in diamond

M. P. Ledbetter,^{1,*} K. Jensen,¹ R. Fischer,² A. Jarmola,¹ and D. Budker^{1,3,†}

¹Department of Physics, University of California at Berkeley, Berkeley, California 94720-7300, USA

²Department of Physics, Technion Israel Institute of Technology, Haifa 32000, Israel

³Nuclear Science Division, Lawrence Berkeley National Laboratory, Berkeley CA 94720, USA

We propose solid-state gyroscopes based on ensembles of negatively charged nitrogen-vacancy (NV^-) centers in diamond. In one scheme, rotation of the nitrogen-vacancy symmetry axis will induce Berry phase shifts in the NV^- electronic ground-state coherences proportional to the solid angle subtended by the symmetry axis. We estimate sensitivity in the range of 5×10^{-3} rad/s/ $\sqrt{\text{Hz}}$ in a 1 mm³ sensor volume using a simple Ramsey sequence. Incorporating dynamical decoupling to suppress dipolar relaxation may yield sensitivity at the level of 10^{-5} rad/s/ $\sqrt{\text{Hz}}$. With a modified Ramsey scheme, Berry phase shifts in the ¹⁴N hyperfine sublevels would be employed. The projected sensitivity is in the range of 10^{-5} rad/s/ $\sqrt{\text{Hz}}$, however the smaller gyromagnetic ratio reduces sensitivity to magnetic-field noise by several orders of magnitude. Reaching 10^{-5} rad/s/ $\sqrt{\text{Hz}}$ would represent an order of magnitude improvement over other compact, solid-state gyroscope technologies.

PACS numbers: 03.65.Vf, 61.72.jn, 06.30.Gv

Inertial sensors form the basis for navigation systems in both military and civilian applications. Such devices also find use in gravity research, for example, in tests of Einstein's equivalence principle [1] or to search for the Lens-Thirring effect [2], a prediction from general relativity of "frame-dragging" in the presence of a massive rotating body. Present state-of-the-art sensors used for navigation in the airline industry are based on the Sagnac effect in fiber-optic bundles, with sensitivity at the level of 2×10^{-8} rad/s/ $\sqrt{\text{Hz}}$ [3]. The same effect in large-area $(\approx m^2)$ ring lasers has yielded sensitivity at the level of 2×10^{-10} rad/s/ $\sqrt{\text{Hz}}$ [4]. Gyroscopes based on cold atom interferometry have also demonstrated sensitivity in the range of 10^{-9} to 10^{-10} rad/s/ $\sqrt{\text{Hz}}$ [2, 5]. Noble gas nuclear spins, which feature long coherence times, can also be used to form rotation sensors [6, 7], with demonstrated sensitivity of about 3×10^{-7} rad/s/ $\sqrt{\text{Hz}}$. Variations on this scheme yield projected sensitivity in the range of 10^{-10} rad/s/ $\sqrt{\text{Hz}}$ [8] in an active volume of several cm³. This concept has been extended to miniaturized versions [9]. Finally, commercially available vibrating microelectromechanical systems (MEMS) gyroscopes achieve sensitivities on the order of 2×10^{-4} rad/s/ $\sqrt{\text{Hz}}$ [10]. Except for the latter two cases, these sensors rely on large volumes or enclosed areas.

Here we propose applying geometric-phase effects in diamond to form gyroscopic sensors from high density ensembles of NV^- centers. The key advantages of NV^- based sensors are their potentially small dimensions and thermal robustness, with the ability to operate from cryogenic temperatures to 600-700 K [11]. Recent theoretical work discusses the possibility of observing large geometric phase shifts in single NV^- centers in diamond [12]. Similar ideas to those proposed here have been discussed

in Ref. [13]. Geometric phase shifts, also known as Berry phase shifts [14], arise when the symmetry axis of a system is rotated about an axis that is not parallel to this axis. This results in relative phase shifts of the magnetic sublevels. One encounters Berry phase shifts, for example, when a spin system evolves in time in the presence of an external magnetic field, which itself rotates in space in such a way that the field vector traces a nonzero solid angle [15]. In the case of adiabatic evolution, an eigenstate with magnetic quantum number m acquires a Berry phase (in addition to the phase due to evolution under the static Hamiltonian) that is given by the product of m and the solid angle traced by the field, $d\Omega$. If the quantization axis is determined by an electric field, a similar effect occurs on rotating the electric field [16]. This is the case for nuclear quadrupoles interacting with an electric-field gradient, and such an effect was used to demonstrate a 131 Xe nuclear-spin gyroscope [17].

The NV⁻ center features a ground state with electronic spin S = 1 which can be initialized, manipulated, and detected via convenient optical and microwave transitions. Furthermore, the lifetime of the ground-state coherences can be quite long, on the order of 2 ms [18] in ¹³C depleted samples, even without applying dynamic decoupling sequences. The analysis presented below indicates that sensitivities at the level of $\approx 10^{-5}$ rad/s/ $\sqrt{\text{Hz}}$ should be achievable in mm scale packages. This falls short of the sensitivities demonstrated by state-of-the-art techniques based on larger sensors, though it surpasses that of commercially available vibrating MEMS sensors. Furthermore, operation as a three-axis sensor may be possible by monitoring coherences in NV⁻ centers with different orientations with respect to the host lattice.

The ground-state level structure of the NV⁻ centers is shown in Fig. 1(a). Detailed discussions of the physics and spectroscopy of this defect can be found in Refs. [19–21] and references therein. NV⁻ centers possess C_{3v} symmetry, and can be oriented along any of the four crystallographic orientations. The electronic ground state is

^{*}Electronic address: micah.ledbetter@gmail.com

[†]Electronic address: dbudker@gmail.com



FIG. 1: (a) Ground-state energy levels of NV⁻ centers in the presence of a magnetic field of several G, and accounting for ¹⁴N hyperfine coupling. The solid, double-headed red arrows show the allowed microwave transitions, which preserve the nitrogen spin, $\Delta m_I = 0$. (b) ¹⁴N hyperfine resolved ODMR spectrum as a function of microwave detuning from *D* for the case of unpolarized (upper trace) and polarized (lower trace) ¹⁴N spins.

spin-triplet (S = 1). In the absence of strain or external magnetic field, the $m_S = \pm 1$ levels are degenerate, where m_S is the quantum number associated with the projection of S along the symmetry axis. Due to the spin-spin interaction, the zero-field splitting between the $m_S = 0$ and $m_S = \pm 1$ levels is D = 2.87 GHz. Application of a magnetic field B_z along the NV⁻ symmetry axis produces a shift of the ground-state energy levels according to $m_S q_s \mu_B B_z$, where $q_s \approx 2$ is the Landé factor for the electron and $\mu_B = 8.79 \text{ rad/s/G}$ is the Bohr magneton. (We focus here on a single orientation, assumed parallel to the magnetic field. The projection of such a magnetic field onto the other three axes is suppressed by a factor of 3. Therefore, for sufficiently large magnetic fields, ≈ 10 G, the microwave transitions of differently oriented NV⁻ centers are well isolated from NV⁻ centers whose symmetry axis is parallel to the field. Since microwave transitions are excited resonantly, we can ignore the contributions from these other orientations.) In the presence of local strain, the $m_S = \pm 1$ sublevels are mixed and the corresponding eigenstates are split in energy by 2E, where E is the transverse zero-field splitting parameter, typically on the order of a few MHz for high NV⁻ density samples. Application of magnetic fields of several gauss will overwhelm this, so that eigenstates are approximately those of S_z . Finally, hyperfine coupling of the ¹⁴N nuclear spin (I = 1) to the electronic degrees of freedom produces additional splittings as shown at the right of Fig. 1(a).

Optically detected magnetic resonance (ODMR) spec-

troscopy of the ground state can be accomplished as follows: Optical transitions from the ${}^{3}A_{2}$ ground states to the ${}^{3}E$ excited-state manifold are spin-conserving, preserving the magnetic quantum number m_S , and are typically excited via the phonon sideband (PSB) of the ${}^{3}A_{2} \rightarrow {}^{3}E$ transition using 532 nm light. Optical pumping of the $m_S = 0$ ground state occurs through spin non-conserving decay pathways (due to spin-orbit coupling) involving singlet levels not shown in Fig. 1. Fluorescence in the zero-phonon line (ZPL) at 637 nm and the associated PSB is brighter for NV^- starting in the $m_S = 0$ state. Thus, application of microwaves tuned to the $m_S = 0 \rightarrow m_S = \pm 1$ ground-state transitions depopulates the $m_S = 0$ state and reduces fluorescence in the ZPL and its PSB. Assuming the NV⁻ center is aligned with the magnetic field, and neglecting ¹⁴N hyperfine coupling, fluorescence as a function of microwave frequency appears as a doublet, centered about D, with a splitting determined by the magnetic field $\Delta = 2g_s \mu_B B_z$ (assuming $g_s \mu_B B_z \gg E$). If ¹⁴N hyperfine coupling is resolved, each line of the doublet splits into a triplet. ODMR spectra are schematically shown in Fig. 1(b) for unpolarized and polarized ¹⁴N spins (top and bottom traces, respectively). The polarization of nuclear spins involves elevated magnetic fields (see below), however, this plot assumes observation in a magnetic field $\approx 10 \text{ G}$ in both cases. One can also detect the spin state by monitoring transmission of infrared light tuned to the 1042 nm transition between the two singlet levels, resulting in improved light collection [22].

 NV^- electronic Berry phase based gyroscopes – We first neglect ¹⁴N hyperfine coupling and suppose an ensemble of NV⁻ centers is pumped into the $m_S = 0$ state, with a magnetic field (approx 10 G) applied along the NV⁻ axis. Suppose the diamond is rotated with an angular velocity ω about an axis z' oriented at an angle θ relative to the NV⁻ symmetry axis ($\theta \leq \pi/2$) during some interval t(Fig. 2). The symmetry axis thus traces a solid angle

$$\Omega = \int_{\phi=0}^{\omega t} \int_{\theta'=0}^{\theta} d\phi d\theta' \sin \theta' = \omega t (1 - \cos \theta).$$
 (1)

In the course of this rotation, the Zeeman eigenstates of the NV⁻ center pick up a geometric phase shift $\Delta \phi = m_S \Omega$. From Eq. (1), we see that this geometric phase shift is maximized for $\theta = \pi/2$. If one establishes coherences between $m_S = 0$ and $m_S = \pm 1$ states prior to rotation, the observed transition frequencies will be $\omega_{\pm} = 2\pi D \pm g_s \mu_B B \pm \omega (1 - \cos \theta)$.

The observed frequency shifts associated with rotations involve both the rotation rate ω and the angle of rotation with respect to the NV⁻ symmetry axis, θ . If the magnetic field is oriented such that resonances due to all four NV⁻ orientations are resolved, Berry phase shifts in the four different orientations can be used to determine both the direction of rotation and its magnitude.

One can envision several schemes for readout. Here, we consider a Ramsey scheme, in which NV⁻ centers are initialized in the $m_S = 0$ sublevel by application of 532



FIG. 2: Rotation of diamond about an axis z' oriented at an angle θ with respect to the NV⁻ symmetry axis.

nm pump light. A $\pi/2$ microwave pulse is applied to the spins, they are allowed to precess freely for a time t, and then a second $\pi/2$ pulse is applied, converting coherences back into populations. Finally the spin state is read out by monitoring fluorescence while illuminating the sample with 532 nm pump light. The resulting fluorescence is given by

$$F \approx \eta N (1 + R \cos \omega_{\pm} t). \tag{2}$$

Here, R is the detection contrast for states with $m_S = 0$ and $m_S = \pm 1$, η is the collection efficiency, and N is the number of participating NV⁻ centers. This assumes a roughly optimal readout, in which each center emits one photon in the readout stage. The slope of the fluorescence with respect to rotation rate ω (assuming ω is small) is maximized by tuning B and t such that $(2\pi D + g_s \mu_B B)t = (n \pm 1/4)2\pi$, where n is an integer, thereby optimizing the sensitivity to rotations. Under such conditions $dF/d\omega \approx \pm \eta NRt$. The accuracy with which one can determine the rotation frequency ω is $\delta\omega = (dF/d\omega)^{-1}\delta F$. Fundamentally limiting the noise in the fluorescence is photon shot noise, $\delta F = \sqrt{\eta N}$. Setting $t = T_2^*$, and repeating the measurement τ/T_2^* times (τ is the total integration time), we find

$$\delta\omega = 1/(R\sqrt{\eta N T_2^{\star}\tau}). \tag{3}$$

Realistic parameters may be conservatively estimated based on Ref. [23], where NV⁻ ensembles were realized with density of $n = 10^{18}$ cm⁻³, $T_2^* \approx 300$ ns, and a measurement volume of 1 mm³. Fluorescence detection suffers from poor contrast ratio and poor detection efficiency (typically $R \approx 0.03$ and $\eta \approx 0.01$). The detection efficiency can be substantially improved to $\eta \approx 1$ by employing IR absorption [22], or by using the side collection technique demonstrated in Ref. [24], where $\eta \approx 0.5$ was realized. Assuming $\eta = 0.5$, 1/4 of the NV⁻ centers participating, a measurement volume of 1 mm³, and a measurement time $\tau = 0.5$ s (corresponding to a bandwidth of 1 Hz), Eq. (3) yields rotation sensitivity of about 5.4×10^{-3} rad/s/ $\sqrt{\text{Hz}}$. This is below the demonstrated sensitivity of the state-of-the-art sensors mentioned above, however, the active part of the sensor is smaller by several orders of magnitude.

The numbers given above are fairly conservative. Reference [25] reports that CPMG decoupling sequences can be used to extend coherence times by an order of magnitude when ¹⁴N impurities limit the lifetime. More recent work has shown coherence lifetimes as long as 300 ms in low NV⁻ density samples in isotopically pure ¹²C diamond using a CPMG decoupling sequence at 77 K [26]. For the work reported in Ref. [23], dipole-dipole coupling between NV⁻ centers appeared to limit the lifetime. As suggested in Ref. [27], such relaxation may be mitigated by pulse sequences such as MREV [28] or WAHUHA [29], which average the dipole-dipole interaction to zero and scale the rank-1 gyroscopic phase shift (for WAHUHA, the scaling factor is $1/\sqrt{3}$). Ultimately, T_1 places an upper bound on T_2 . In Ref. [30] room-temperature measurements of $T_1 = 3$ ms was measured for the high NV⁻ density samples of present interest. Assuming dipoledipole relaxation can be sufficiently suppressed in highdensity ensembles, one can expect roughly two orders of magnitude improvement in sensitivity over the estimate given above, placing the sensitivity in the range of 10^{-5} rad/s/ $\sqrt{\text{Hz}}$.

Magnetic-field fluctuations present a serious source of noise in this scheme. The sensitivity to magnetic field fluctuations is given by $\delta \omega = (\partial F/\partial \omega)^{-1} (\partial F/\partial B) \delta B =$ $g_s \mu_B \delta B$. In order to reach an angular-frequency sensitivity of 5.4×10^{-3} rad s⁻¹, one requires magnetic field stability $\delta B \approx 3 \times 10^{-10}$ G. Assuming ≈ 10 G is required to sufficiently suppress the stress parameter, this corresponds to fractional field stability at the level of 10^{-10} , challenging, though not insurmountable.

The temperature dependence of the D coefficient places substantial requirements on thermal stability. The temperature dependence of D near room temperature is linear [31], with a slope of about -70 kHz/K. To reach 10^{-3} rad/s/ $\sqrt{\text{Hz}}$ requires thermal stability at the level of 10^{-9} K. Such stability seems unrealistic, however, if one monitors the splitting of the ODMR signal for $m_S = \pm 1$ rather than the position of just a single line, the temperature dependence should be eliminated. This also improves the sensitivity of the gyroscope by a factor of $\sqrt{2}$.

Nuclear spin based diamond gyroscopes – Nuclear spins are appealing in the context of gyroscopes because their gyromagnetic ratio is about three orders of magnitude smaller than that of the electron, relaxing the requirements on field stability. Recent work has shown that it is possible to achieve very high, $\approx 98\%$, polarization of single ¹⁴N or ¹⁵N nuclear spins in the NV⁻ center (as well as nearby ¹³C spins) using an excited-state level anticrossing at about 500 G, induced by the hyperfine coupling of the nucleus with the electrons of the center [32, 33]. This



FIG. 3: Pulse sequence for Berry phase based gyroscope using resolved 14 N hyperfine structure in diamond.

technique has been extended to polarization of ¹⁴N and proximal ¹³C nuclear spins in ensembles of NV⁻ centers [34]. The ¹⁴N spin state can be detected via fluorescence or IR absorption by the NV⁻ center.

An experimental protocol for a ¹⁴N diamond based gyroscope is presented in Fig. 3. NV^- centers are polarized in the $|m_S = 0, m_I = -1\rangle$ state by turning the magnetic field (oriented parallel to the NV⁻ symmetry axis) up to about 500 G, while illuminating the sample with 532 nm light (see Refs. [32, 34]). The light is turned off, and the magnetic field reduced to about 10 G (to improve stability), and coherences between the $|m_S = 0, m_I = -1\rangle$ and $|m_S = 0, m_I = 0\rangle$ ground state sublevels are established by application of a $\pi/2$ pulse, resonantly tuned to the hyperfine transition frequency $\omega_{hf} \approx 5.1$ MHz. Spins are allowed to evolve freely for some time t in the presence of the magnetic field, hyperfine coupling, and sample rotation, accruing both nuclear Zeeman, hyperfine, and geometric phase shifts. A second $\pi/2$ pulse converts these coherences back into ¹⁴N Zeeman-sublevel populations, which are then selectively read out by applying microwaves tuned to the desired ¹⁴N hyperfine transition, indicated by either of the downwards pointing arrows in Fig. 1(b). Population in the selected level would oscillate sinusoidally with a frequency proportional to $\omega_{nuc} = \omega_{hf} + \gamma_N B + \omega$ where γ_N is the gyromagnetic ratio of the nitrogen nucleus (we have set $\theta = \pi/2$ so that the factor $1 - \cos \theta$ in Eq. (1) is equal to 1). Since the microwave and optical transitions preserve m_I , this results in a sinusoidal modulation of the resulting fluorescence F

$$F \propto 1 + R \frac{\Delta B^2}{(B - B_0)^2 + \Delta B^2} \cos \omega_{nuc} t.$$
 (4)

Here, B_0 is the magnetic field corresponding to resonance with the applied microwaves and $\Delta B = 1/(T_2^* g_s \mu_B)$ is the width of the microwave transition in magnetic field units. The Lorentzian profile for the microwaves is included to address the possibility of noise due to magnetic field fluctuations. As we see below, it turns out that this factor drops out. The same arguments used to derive the sensitivity, Eq. (3), of gyroscopes based on pure electronic transitions applies in this case as well.

The exact value of T_2^* will depend on conditions and sample preparation. We point out that in some instances, the nuclear spin coherence times $T_{2,nuc}^*$ can be significantly longer for nuclear spins than for electron spins. For example, with single NV⁻ centers, Ref. [35] reports, $T_{2,e}^* \approx 1.4 \ \mu s$, while $T_{2,nuc}^* \approx 58 \ \mu s$ for ¹⁴N spins. In ¹³C depleted diamonds with low NV⁻ density, ¹⁴N coherence lifetimes $T_2^* = 7$ ms have been realized [36]. Measurements of these quantities in high-density samples are planned. Taking $T_{2,nuc}^* = 1$ ms, equation (3) yields sensitivity at the level of $9 \times 10^{-5} \ rad/s/\sqrt{Hz}$, with other parameters as used above, and without requiring dynamical decoupling.

Despite the fact that microwave transitions are used to selectively read out the nuclear spin state, the sensitivity to magnetic field fluctuations is dramatically reduced compared to the case of gyroscopes based solely on electronic transitions: $\delta \omega = (\partial F/\partial \omega)^{-1} (\partial F/\partial B) \delta B =$ $\gamma_N \delta B$. We see that this is suppressed relative to the case of electronic coherences by a factor of $\gamma_N/(g_s \mu_B) \approx 9000$ for ¹⁴N, greatly relaxing the requirements on field stability.

In summary, we have proposed a new type of solidstate gyroscope based on Berry-phase effects in diamond nitrogen-vacancy centers. We estimate that the sensitivity of such a device could surpass that of commercial vibrating MEMS sensors, which find wide application in a variety of technologies. We also point out that NV⁻ centers have been used to polarize bulk ¹³C in elevated magnetic fields [37], and efforts are under way to produce polarization of bulk ¹³C nuclear spins in low magnetic field. Bulk ¹³C spins can potentially have very long T_1 times [38], and if decoupling schemes can yield correspondingly long T_2^* times, one may expect dramatic improvements in sensitivity.

This work was supported by AFOSR/DARPA QuASAR, and by the NSF Grant PHY - 0855552. K.J. acknowledges support from the Danish Council for Independent Research. The authors thank V. M. Acosta and A.O. Sushkov for invaluable discussions.

- H. Müller, A. Peters, and S. Chu, Nature, 463, 926 (2010).
- [2] C. Jentsch, T. Müller, E.M. Rasel, and W. Ertmer, Gen.

Relativ. Gravit. 36, 2197 (2004).

- [3] S. J. Sanders, L. K. Strandjord, and D. Mead, in 15th Optical Fiber Sensors Conference Tech. Digest (IEEE, Portland, 2002), p. 5.
- [4] G. E. Stedman, K. U. Schreiber, and H. R. Bilger, Classical Quantum Gravity 20, 2527 (2003).
- [5] T. L. Gustavson, A. Landragin, and M. A. Kasevich, Classical Quantum Gravity 17, 2385 (2000).
- [6] B. C. Grover, E. Kanegsberg, J. Mark, R. L. Meyer, Litton Systems, Inc., "Nuclear Magnetic Resonance Gyro", U.S. Patent 4,157,495, June 5, 1979.
- [7] Michael Larsen, "Nuclear Magnetic Resonance Gyroscope", poster presentation, meeting of the Division of Atomic Molecular and Optical Physics (2012).
- [8] T. W. Kornack, R. K. Ghosh, and M. V. Romalis, Phys. Rev. Lett. 95, 230801 (2005).
- [9] L. Lust and D. W. Youngner, "Chip scale atomic gyroscope," U.S. Patent 7,359,059, Apr. 15, 2008.
- [10] Invensense, www.invensense.com.
- [11] D. M. Toyli *et al.*, arXiv:1201.4420.
- [12] D. Maclaurin, M. W. Doherty, L. C. L. Hollenberg, and A. M. Martin, Phys. Rev. Lett. **108**, 240403 (2012).
- [13] A. Ajoy, P. Cappellaro, arXiv:1205.1494 (2012).
- [14] M. V. Berry, Proc. R. Soc. Lond. A 392, 45-57 (1984).
- [15] E. Commins, Am. J. Phys. 59, 1077 (1991).
- [16] D. Budker, D. DeMille, D.F. Kimball, Atomic Physics, 2ⁿd Ed. (Oxford University Press, New York, 2008)
- [17] S. Appelt, G. Wäckerle, and M. Mehring, Phys. Rev. Lett. 72, 3921 (1994).
- [18] G. Balasubramanian et al., Nature Materials 8, 383 (2009).

- [19] N. B. Manson, J. P. Harrison, and M. J. Sellars, Phys. Rev. B 74, 104303 (2006).
- [20] L. G. Rogers, S. Armstrong, M. J. Sellars, and N. B. Manson, New J. Phys. **10**, 103024 (2008).
- [21] M. W. Doherty et al., Phys. Rev. B 85, 205203 (2012).
- [22] V. M. Acosta et al., Appl. Phys. Lett. 97, 174104 (2010).
- [23] V. M. Acosta *et al.*, Phys. Rev. B **80**, 115202 (2009).
- [24] D. Le Sage *et al.*, Phys. Rev. B **85**, 121202 (2012).
- [25] L. M. Pham et al., Phys. Rev. B 86, 045214 (2012).
- [26] N. Bar-Gill, L. M. Pham, A. Jarmola, D. Budker, and R. Walsworth, manuscript in preparation.
- [27] J. M. Taylor et al., Nat. Phys. 4, 810 (2008).
- [28] P. Mansfield, J. Phys. C 4, 14441452 (1971).
- [29] J. S. Waugh, L. M. Huber, U. Haberlein, Phys. Rev. Lett. 20, 180 (1968).
- [30] A. Jarmola, V. M. Acosta, K. Jensen, S. Chemerisov, and D. Budker, Phys. Rev. Lett. **108**, 197601 (2012).
- [31] V. M. Acosta et al., Phys. Rev. Lett. 104, 070801 (2010).
- [32] V. Jacques et al., Phys. Rev. Lett. 102, 057403 (2009).
- [33] B. Smeltzer, J. McIntyre, and L. Childress, Phys. Rev. A 80, 050302 (2009).
- [34] R. Fisher, A. Jarmola, P. Kehayias, and D. Budker, arXiv:1202.1072.
- [35] G. D. Fuchs, G. Burkard, P. V. Klimov, and D. D. Awschalom, Nat. Phys. 10, 789 (2011).
- [36] G. Waldherr et al., Nat. Nanotech 7, 105 (2012).
- [37] J. P. King, P. J. Coles, and J. A. Reimer, Phys. Rev. B 81, 073201 (2010).
- [38] K. Lefmann et al., Phys. Rev. B 50, 15623 (1994).