

## CHCRUS

This is the accepted manuscript made available via CHORUS. The article has been published as:

High-Fidelity Controlled-math xmlns="http://www.w3.org/1998/Math/MathML" display="inline">mi>Z/mi>/math> Gate with Maximal Intermediate Leakage Operating at the Speed Limit in a Superconducting Quantum Processor V. Negîrneac, H. Ali, N. Muthusubramanian, F. Battistel, R. Sagastizabal, M. S. Moreira, J. F. Marques, W. J. Vlothuizen, M. Beekman, C. Zachariadis, N. Haider, A. Bruno, and L. DiCarlo Phys. Rev. Lett. **126**, 220502 — Published 4 June 2021 DOI: 10.1103/PhysRevLett.126.220502

## High-fidelity controlled-Z gate with maximal intermediate leakage operating at the speed limit in a superconducting quantum processor

V. Negîrneac,  $^{1,\,2,\,*}$  H. Ali,  $^{1,\,3,\,*}$  N. Muthusubramanian,  $^{1,\,3}$  F. Battistel,  $^{1}$ 

R. Sagastizabal,<sup>1,3</sup> M. S. Moreira,<sup>1,3</sup> J. F. Marques,<sup>1,3</sup> W. J. Vlothuizen,<sup>1,4</sup>

M. Beekman,<sup>1,4</sup> C. Zachariadis,<sup>1,3</sup> N. Haider,<sup>1,4</sup> A. Bruno,<sup>1,3</sup> and L. DiCarlo<sup>1,3</sup>

<sup>1</sup>QuTech, Delft University of Technology, P.O. Box 5046, 2600 GA Delft, The Netherlands

<sup>2</sup>Instituto Superior Técnico, Lisbon, Portugal

<sup>3</sup>Kavli Institute of Nanoscience, Delft University of Technology,

P.O. Box 5046, 2600 GA Delft, The Netherlands

<sup>4</sup>Netherlands Organisation for Applied Scientific Research (TNO),

P.O. Box 96864, 2509 JG The Hague, The Netherlands

(Dated: April 29, 2021)

Simple tuneup of fast two-qubit gates is essential for the scaling of quantum processors. We introduce the sudden variant (SNZ) of the Net Zero scheme realizing controlled-Z (CZ) gates by flux control of transmon frequency. SNZ CZ gates realized in a multi-transmon processor operate at the speed limit of transverse coupling between computational and non-computational states by maximizing intermediate leakage. Beyond speed, the key advantage of SNZ is tuneup simplicity, owing to the regular structure of conditional phase and leakage as a function of two control parameters. SNZ is compatible with scalable schemes for quantum error correction and adaptable to generalized conditional-phase gates useful in intermediate-scale applications.

Superconducting quantum processors have recently reached important milestones [1], notably the demonstration of quantum supremacy on a 53-transmon processor [2]. On the path to quantum error correction (QEC) and fault tolerance [3], recent experiments have used repetitive parity measurements to stabilize twoqubit entanglement [4, 5] and to perform surface-code quantum error detection in a 7-transmon processor [6]. These developments have relied on two-qubit controlledphase (CPhase) gates realized by dynamical flux control of transmon frequency, harnessing the transverse coupling  $J_2$  between a computational state  $|11\rangle$  and a non-computational state such as  $|02\rangle$  [7, 8]. Compared to other implementations, e.g., cross-resonance using microwave-frequency pulses [9] and parametric radiofrequency pulsing [10], baseband flux pulses achieve the fastest controlled-Z (CZ) gates (a special case of CPhase), operating near the speed limit  $t_{\text{lim}} = \pi/J_2$  [11].

Over the last decade, baseband flux pulsing for twoqubit gating has evolved in an effort to increase gate fidelity and to reduce leakage and residual ZZ coupling. In particular, leakage became a main focus for its negative impact on QEC, adding complexity to errordecoder design [12] and requiring hardware and operational overhead to seep [13–17]. To reduce leakage from linear-dynamical distortion in flux-control lines and limited time resolution in arbitrary waveform generators (AWGs), unipolar square pulses [8, 18] have been superseded by softened counterparts [19, 20] based on fastadiabatic theory [21]. In parallel, coupling strengths have reduced to  $J_2/2\pi \sim 10-20$  MHz to mitigate residual ZZ coupling, which affects single-qubit gates and idling at bias points, and produces crosstalk from spectator qubits [22]. Many groups are actively developing tunable coupling schemes to suppress residual coupling without incurring slowdown [23–27].

A main limitation to the fidelity of flux-based CPhase gates is dephasing from flux noise, as one qubit is displaced 0.5-1 GHz below its flux-symmetry point (i.e., sweetspot [28]) to reach the  $|11\rangle$ - $|02\rangle$  resonance. To address this limitation, Ref. 29 introduced a bipolar variant [termed Net Zero (NZ)] of the fast-adiabatic scheme, which provides a built-in echo reducing the impact of low-frequency flux noise. The double use of the transverse interaction also reduces leakage by destructive interference, as understood by analogy to a Mach-Zehnder interferometer (MZI). Finally, the zero-average characteristic avoids the buildup of long-timescale distortions in the flux-control lines, significantly improving gate repeatability. NZ pulsing has been successfully used in several recent experiments [4, 6, 30], elevating the state of the art for CZ gate fidelity to  $99.72 \pm 0.35\%$  [1]. However, NZ suffers from complicated tuneup, owing to the complex dependence of conditional phase and leakage on fast-adiabatic pulse parameters. This limits the use of NZ for two-qubit gating as processors grow in qubit count.

In this Letter, we introduce the sudden variant (SNZ) of the NZ scheme implementing CZ, which offers two advantages while preserving the built-in echo, destructive leakage interference, and repeatability characteristic of conventional NZ (CNZ). First, SNZ operates at the speed limit of transverse coupling by maximizing intermediate leakage to the non-computational state. The second and main advantage is greatly simplified tuneup: the land-scapes of conditional phase and leakage as a function of two pulse parameters have regular structure and interrelation, easily understood by exact analogy to the

<sup>\*</sup> These authors contributed equally to this work.

MZI. We realize SNZ CZ gates among four pairs of nearest neighbors in a seven-transmon processor and characterize their performance using two-qubit interleaved randomized benchmarking (2QIRB) with modifications to quantify leakage [29, 31, 32]. The highest performance achieved from one 2QIRB characterization has 99.93  $\pm$  0.24% fidelity and 0.10  $\pm$  0.02% leakage. SNZ CZ gates are fully compatible with scalable approaches to QEC [33]. The generalization of SNZ to arbitrary CPhase gates is straightforward and useful for optimization [34], quantum simulation [35], and other noisy intermediatescale quantum (NISQ) applications [36].

A flux pulse to the  $|11\rangle\text{-}|02\rangle$  interaction implements the unitary

$$U_{\rm CPhase} = \begin{pmatrix} 1 & 0 & 0 & 0 & 0 \\ 0 & e^{i\phi_{01}} & 0 & 0 & 0 \\ 0 & 0 & e^{i\phi_{10}} & 0 & 0 \\ 0 & 0 & 0 & \sqrt{1 - 4L_1}e^{i\phi_{11}} & \sqrt{4L_1}e^{i\phi_{02,11}} \\ 0 & 0 & 0 & \sqrt{4L_1}e^{i\phi_{11,02}} & \sqrt{1 - 4L_1}e^{i\phi_{02}} \end{pmatrix}$$

in the  $\{|00\rangle, |01\rangle, |10\rangle, |11\rangle, |02\rangle\}$  subspace, neglecting decoherence and residual interaction between far offresonant levels. Here,  $\phi_{01}$  and  $\phi_{10}$  are the single-qubit phases,  $\phi_{11} = \phi_{01} + \phi_{10} + \phi_{2Q}$ , where  $\phi_{2Q}$  is the conditional phase, and  $L_1$  is the leakage, The ideal CZ gate simultaneously achieves  $\phi_{01} = \phi_{10} = 0 \pmod{2\pi}$ ,  $\phi_{2Q} = \pi \pmod{2\pi}$  (phase condition PC), and  $L_1 = 0$  (leakage condition LC), with arbitrary  $\phi_{02}$ .

The SNZ CZ gate is realized with two square half pulses with equal and opposite amplitude  $\pm A$  and duration  $t_p/2$  each. To understand its action, consider first the ideal scenario with perfectly square half pulses (infinite bandwidth), infinite time resolution,  $t_p = t_{\rm lim}$ , and A = 1 (corresponding to  $|11\rangle$  and  $|02\rangle$  on resonance). The unitary action of each complete half pulse (rising edge, steady level, and falling edge combined) implements one of two beamsplitters in the MZI analogy: BS1 fully transmits  $|11\rangle$  to  $-i|02\rangle$  (producing maximal intermediate leakage), and BS2 fully transmits  $-i|02\rangle$  to  $-|11\rangle$ , yielding an ideal CZ gate. SNZ adds an idling period  $t_{\phi}$  between the half pulses to perfect the analogy to the MZI, allowing accrual of relative phase  $\phi$  between  $|02\rangle$  and  $|11\rangle$  in between the beamsplitters.

The key advantage of SNZ over CNZ is the straightforward procedure to simultaneously meet PC and LC. To appreciate this, consider the landscapes of  $\phi_{2Q}$  and  $L_1$  as a function of A and  $t_{\phi}$  [Fig. 1(c, d)] in this ideal scenario. The landscapes have a clear structure and link to each other. The  $L_1$  landscape shows a vertical leakage valley at A = 1 arising from perfect transmission at each beamsplitter (LC1), and also two vertical valleys arising from perfect reflection (LC2). Leakage interference gives rise to additional diagonal valleys (LC3). Crucially, juxtaposing the  $\phi_{2Q} = 180^{\circ}$  contour shows that PC is met periodically, at the crossing of LC1 and LC3 valleys, where  $\Delta_{02}^{\max} t_{\phi} = 0 \pmod{2\pi}$  ( $\Delta_{02}^{\max}$  is the detuning between  $|02\rangle$  and  $|11\rangle$  at the bias point). This regular leakage



FIG. 1. Numerical simulation of an ideal SNZ pulse (infinite bandwidth and time resolution) using parameters for pair  $Q_{L}-Q_{M2}$  (see Table 1). (a) Schematic of the ideal SNZ flux pulse, with  $t_p = t_{lim}$  and variable A and  $t_{\phi}$ . The amplitude A is normalized to the  $|11\rangle$ - $|02\rangle$  resonance. Inset: MZI analogy for A = 1. (b) Transition frequency from  $|00\rangle$  to levels  $|ij\rangle$  in the two-excitation manifold as a function of instantaneous pulse amplitude. (c, d) Landscapes of conditional phase  $\phi_{2Q}$  (b) and leakage  $L_1$  (c) as a function of A and  $t_{\phi}$ .

landscape therefore provides useful crosshairs for simultaneously achieving PC and LC. We note that  $\phi_{2Q}(t_{\phi})$ changes monotonically along the LC1 valley, allowing for CPhase gates with arbitrary  $\phi_{2Q}$ . We leave this generalization for future work.

There are practical reasons to include  $t_{\phi}$  in experiment: any flux-pulse distortion remaining from the first half pulse (e.g., due to finite pulse decay time) will break the symmetry between BS1 and BS2. Due to the time resolution  $t_{\rm s}$  of the AWG used for flux control,  $\phi$  can only increment in steps of  $-\Delta_{02}^{\rm max} t_{\rm s}$ . Typically  $\Delta_{02}^{\rm max}/2\pi = 0.5-1$  GHz and  $t_{\rm s} \sim 1$  ns, so the number of intermediate sampling points only provides coarse control. For fine control, we propose to use the amplitude  $\pm B$  of the first and last sampling points during  $t_{\phi}$  [37].

We now turn to the experimental realization of SNZ CZ gates between nearest-neighbor pairs among four transmons. High- and low-frequency transmons ( $Q_H$  and  $Q_L$ , respectively) connect to two mid-frequency transmons ( $Q_{M1}$  and  $Q_{M2}$ ) using bus resonators dedicated to each pair [connectivity diagram shown in Fig. 4(a) inset]. Each transmon has a flux-control line for two-qubit gating, a microwave-drive line for single-qubit gating, and dedicated readout resonators [4, 38] (see [37] for details). Each transmon is statically flux-biased at its sweetspot to



FIG. 2. Calibration of the SNZ pulse for pair  $Q_{\rm L}$ - $Q_{\rm M2}$  and comparison to simulation. (a)  $|2\rangle$ -state population of  $Q_{\rm M2}$ as a function of the amplitude and duration of a unipolar square pulse making  $|11\rangle$  interact with  $|02\rangle$ . (b,c) Landscapes of conditional phase  $\phi_{2\rm Q}$  and leakage estimate  $\tilde{L}_1$  as a function of SNZ pulse amplitudes A and B, with  $t_{\phi} = 1.67$  ns. The juxtaposed  $\phi_{2\rm Q} = 180^{\circ}$  contour runs along the opposite diagonal compared to Figs. 1(b,c) because increasing B (which decreases  $\Delta_{02}$ ) changes  $\phi$  in the opposite direction from  $t_{\phi}$ . Data points marked with dots are measured with extra averaging for examination in Fig. 3. (d) Numerical simulation of leakage  $L_1$  landscape and  $\phi_{2\rm Q} = 180^{\circ}$  contour with parameters and flux-pulse distortions from experiment. All landscapes (also in Fig. 3) are sampled using an adaptive algorithm based on [40].

counter residual offsets. Flux pulsing is performed using a Zurich Instruments HDAWG-8 ( $t_s = 1/2.4$  ns). Following prior work [29, 39], we compensate the bandwidthlimiting effect of attenuation in the flux-control coaxial line (skin effect) and cryogenic reflective and absorptive low-pass filters using real-time digital filters in the AWG. In this way, we produce on-chip flux waveforms with rise time  $t_{rise}$  on par with that of the AWG (0.5 ns).

We exemplify the tuneup of SNZ using pair  $Q_L-Q_{M2}$ (Fig. 2). We first identify  $t_{\rm lim}$  for the  $|11\rangle$ - $|02\rangle$  interaction and amplitude A bringing the two levels on resonance. Both are extracted from the characteristic chevron pattern of  $|2\rangle$ -population  $P_{|2\rangle}$  in  $Q_{M2}$  as a function of the amplitude and duration of a unipolar square flux pulse acting on  $|11\rangle$  [Fig. 2(a)]. The symmetry axis corresponds to A = 1. The difference in consecutive pulse durations achieving  $P_{|2\rangle}$  maxima along this axis gives an accurate estimate of  $t_{\rm lim}$  unaffected by initial transients. We set  $t_{\rm p} \equiv 2nt_{\rm s}$ , where n is the number of sampling points achieving the first  $P_{|2\rangle}$  maximum. Using the measured positive difference  $t_{\rm p} - t_{\rm lim}$  and numerical simula-



FIG. 3. (a,b) Landscapes of the leakage estimate  $\tilde{L}_1$  for intentionally short and long SNZ half pulses on  $Q_{M2}$ . (c) Extracted  $\tilde{L}_1$  along the  $\phi_{2Q} = 180^{\circ}$  contours from (a), (b), and Fig. 2(c).

tion (data not shown), we estimate  $t_{\rm rise} \approx 0.5$  ns. Next, we use standard conditional-oscillation experiments [29] to measure the landscapes of  $\phi_{2\rm Q}$  and leakage estimate  $\tilde{L}_1$ for SNZ pulses over amplitude ranges  $A \in [0.9, 1.1]$  and  $B \in [0, A]$ , keeping  $t_{\phi} \gtrsim 3t_{\rm rise}$ . As expected, the landscape of  $\tilde{L}_1$  [Fig. 2(c)] reveals a vertical valley at A = 1and a diagonal valley. Juxtaposing the  $\phi_{2\rm Q} = 180^\circ$  contour from Fig. 2(b), we observe the matching of PC at the crossing of these valleys, in excellent agreement with a numerical two-qutrit simulation [Fig. 2(d)].

Experimentally, due to the discreteness of  $t_s$ , it is unlikely to precisely match  $t_{\rm p}/2$  to the half-pulse duration that truly maximizes  $P_{|2\rangle}$ . To understand the consequences, we examine the  $\phi_{2Q}$  and  $\hat{L}_1$  landscapes for SNZ pulses upon intentionally changing  $t_p$  by  $\pm 6t_s$  (Fig. 3). While the PC contour remains roughly unchanged in both cases, there are significant effects on  $L_1$ . In both cases, we observe that  $L_1$  lifts at the prior crossing of LC1 and LC3 valleys where  $\phi_{2Q} = 180^{\circ}$ . For too-short pulses [Fig. 3(a)], there remain two valleys of minimal  $\hat{L}_1$ , but these are now curved and do not cross  $\phi_{2Q} = 180^{\circ}$ . For too-long pulses [Fig. 3(b)], there are also two curved valleys. Crucially, these cross the  $\phi_{2Q} = 180^{\circ}$  contour, and it remains possible to achieve PC and minimize leakage at two (A, B) settings. Extracting  $\tilde{L}_1$  along the  $\phi_{2Q} = 180^{\circ}$  contours [Fig. 3(c)] confirms that too-long pulses can achieve the same minimal  $L_1$  as when using the nominal  $t_{\rm p}$ . The impossibility to achieve minimal leakage at  $\phi_{2Q} = 180^{\circ}$  for too-short pulses manifests the speed limit set by  $J_2$ . In turn, the demonstrated possi-

Parameter	$\rm Q_{M1}\text{-}Q_{H}$	$Q_{M2}$ - $Q_H$	$Q_{\rm L}\text{-}Q_{\rm M1}$	$\rm Q_L\text{-}Q_{M2}$
$t_{\rm lim}$ (ns)	31.0	27.6	38.4	33.8
$t_{\rm p}, t_{\phi} \ ({\rm ns})$	32.50, 2.92	$29.10, \ 3.75$	40.83, 1.25	35.83, 1.67
$t_{\rm total} \ ({\rm ns})$	45.42	42.91	52.08	47.50
Interaction	$ 11\rangle$ - $ 02\rangle$	$ 11\rangle$ - $ 02\rangle$	$ 11\rangle$ - $ 20\rangle$	$ 11\rangle$ - $ 02\rangle$
Parked qubit	$Q_{M2}$	$Q_{M1}$	-	—
Avg. $F$ (%)	$98.89 \pm 0.35$	$99.54 \pm 0.27$	$93.72 \pm 2.10$	$97.14 \pm 0.72$
Avg. $L_1$ (%)	$0.13\pm0.02$	$0.18\pm0.04$	$0.78\pm0.32$	$0.63\pm0.11$
Max. $F(\%)$	$99.77 \pm 0.23$	$99.93 \pm 0.24$	$99.15 \pm 1.20$	$98.56 \pm 0.70$
Min. $L_1$ (%)	$0.07\pm0.04$	$0.10\pm0.02$	$0.04\pm0.08$	$0.41\pm0.10$

TABLE I. Summary of SNZ CZ pulse parameters and achieved performance for the four transmon pairs. Singlequbit phase corrections are included in  $t_{\text{total}}$ . Gate fidelities and leakage are obtained from 2QIRB keeping the other two qubits in  $|0\rangle$ . Statistics (average and standard deviation) are taken from repeated 2QIRB runs (see [37] for technical details). The maximum F and minimum  $L_1$  quoted are not necessarily from the same run.

bility to do so for too-long pulses (even overshooting by several sampling points) proves the viability of the SNZ pulse in practice.

With these insights, we proceed to tune the remaining SNZ CZ gates following similar procedures. We use final weak bipolar pulses of total duration  $t_{1Q} = 10$  ns to null the single-qubit phases in the frame of microwave drives. Since our codeword-based control electronics has a 20 ns timing grid, and 40 ns  $< t_{\text{total}} = t_{\text{p}} + t_{\phi} + t_{1\text{Q}} < 60$  ns for all pairs, we allocate 60 ns to every CZ gate. Some pairspecific details must be noted. Owing to the frequency overlap of  $Q_{M1}$  and  $Q_{M2}$ , implementing CZ between  $Q_H$ and  $Q_{M1}$  ( $Q_{M2}$ ) requires a bipolar parking flux pulse on  $Q_{M2}(Q_{M1})$  during the SNZ pulse on  $Q_H$  [6, 33]. For most pairs, we employ the  $|11\rangle - |02\rangle$  interaction, which requires the smallest flux amplitude (reducing the impact of dephasing from flux noise) and does not require crossing any other interaction. However, for Q<sub>L</sub>-Q<sub>M1</sub>, we cannot reliably use this interaction as there is a flickering twolevel system (TLS) overlapping with the  $|0\rangle$ - $|1\rangle$  transition in  $Q_{M1}$  at this amplitude [37]. For this pair, we therefore employ the  $|11\rangle$ - $|20\rangle$  interaction. Here, SNZ offers a side benefit: it crosses the  $Q_{M1}$ -TLS,  $|11\rangle$ - $|02\rangle$ , and  $|01\rangle$ - $|10\rangle$ resonances as suddenly as possible, minimizing population exchange.

Table 1 summarizes the timing parameters and performance attained for the four SNZ CZ gates. The CZ gate fidelity F and leakage  $L_1$  are extracted using a 2QIRB protocol [29, 32]. For each pair, we report the average and standard deviation of both based on at least 10 repetitions of the protocol spanning more than 8 h [37]. Several observations can be drawn. First, CZ gates involving  $Q_H$  perform better on average than those involving  $Q_L$ . This is likely due to the shorter  $t_{\rm lim}$  and correspondingly longer time 60 ns  $-t_p$  spent near the sweetspot. Additionally, the frequency downshifting required of  $Q_H$ to interact with the mid-frequency transmons is roughly half that required of the latter to interact with  $Q_L$ . This reduces the impact of dephasing from flux noise during



FIG. 4. Best SNZ CZ gate performance achieved from a single run of 2QIRB. (a) Reference and CZ-interleaved return probability  $M_0$  to  $|00\rangle$  and (b) population in the computational space  $\chi_1$  as a function of the number of two-qubit Cliffords in the reference curve. Errors bars in F and  $L_1$  are obtained from the uncertainty of exponential-decay fits.

the pulse. Not surprisingly, performance is worst for  $Q_{L}-Q_{M1}$ . Here, the pulse must downshift  $Q_{M1}$  the most to reach the distant  $|11\rangle$ - $|20\rangle$  interaction, increasing dephasing from flux noise. Also, there may be residual exchange at the crossed resonances. Overall, there is significant temporal variation in performance as gleaned by repeated 2QIRB characterizations. We believe this reflects the underlying variability of qubit relaxation and dephasing times and flux offsets, which however were not tracked simultaneously. In addition to having the best average performance, pair  $Q_{M2}$ - $Q_H$  displays the maximum F of 99.93  $\pm$  0.24% (Fig. 4) extracted from a single 2QIRB characterization. To the best of our knowledge, this is the highest CZ fidelity extracted from one 2QIRB characterization in a multi-transmon processor.

To understand the dominant sources of infidelity  $\varepsilon = 1 - F$  and leakage, we run numerical simulations [29], for both SNZ and CNZ, with experimental input parameters for pair Q<sub>M2</sub>-Q<sub>H</sub>. We dissect an error budget versus various models finding similar contributions for both gates (see [37]). Nevertheless, the results suggest that SNZ slightly outperforms CNZ, likely due to a shorter time spent away from the sweetspot during the fixed 60 ns allocated for both variants. This confirms that the temporary full transfer from  $|11\rangle$  to  $|02\rangle$  does not compromise the gate fidelity.

In summary, we have proposed and realized highfidelity CZ gates using the sudden version of the Net Zero bipolar fluxing scheme. SNZ CZ gates operate ever closer to the speed limit of transverse coupling by maximizing intermediate leakage to the non-computational state. Control architectures without a timing grid will benefit most from the speedup of SNZ over CNZ by reducing total gate time and thereby minimizing the impact of decoherence. A demonstrated second key advantage of SNZ over CNZ is ease of tuneup, owing to the simple structure of error landscapes as a function of pulse parameters. Harnessing the tuning simplicity, we already employ SNZ CZ gates in the Starmon-5 processor publicly available via the QuTech Quantum Inspire platform [41]. Moving forward, the compatibility of SNZ with our scalable scheme [33] for surface coding makes SNZ our choice for CZ gates for quantum error correction. Finally, the straightforward extension of SNZ to arbitrary conditional-phase gates will find immediate use in NISQ applications.

Data availability: Interested readers can reproduce our figures by using the processed data of the figures. The processed data can be found at https://github.com/DiCarloLab-Delft/ High\_Fidelity\_ControlledZ\_Data/.

- M. Kjaergaard, M. E. Schwartz, J. Braumller, P. Krantz, J. I.-J. Wang, S. Gustavsson, and W. D. Oliver, Annual Review of Condensed Matter Physics 11, 369 (2020).
- [2] F. Arute, K. Arya, R. Babbush, D. Bacon, J. C. Bardin, R. Barends, R. Biswas, S. Boixo, F. G. S. L. Brandao, D. A. Buell, B. Burkett, Y. Chen, Z. Chen, B. Chiaro, R. Collins, W. Courtney, A. Dunsworth, E. Farhi, B. Foxen, A. Fowler, C. Gidney, M. Giustina, R. Graff, K. Guerin, S. Habegger, M. P. Harrigan, M. J. Hartmann, A. Ho, M. Hoffmann, T. Huang, T. S. Humble, S. V. Isakov, E. Jeffrey, Z. Jiang, D. Kafri, K. Kechedzhi, J. Kelly, P. V. Klimov, S. Knysh, A. Korotkov, F. Kostritsa, D. Landhuis, M. Lindmark, E. Lucero, D. Lyakh, S. Mandrà, J. R. Mc-Clean, M. McEwen, A. Megrant, X. Mi, K. Michielsen, M. Mohseni, J. Mutus, O. Naaman, M. Neeley, C. Neill, M. Y. Niu, E. Ostby, A. Petukhov, J. C. Platt, C. Quintana, E. G. Rieffel, P. Roushan, N. C. Rubin, D. Sank, K. J. Satzinger, V. Smelvanskiv, K. J. Sung, M. D. Trevithick, A. Vainsencher, B. Villalonga, T. White, Z. J. Yao, P. Yeh, A. Zalcman, H. Neven, and J. M. Martinis, Nature 574, 505 (2019).
- [3] A. G. Fowler, M. Mariantoni, J. M. Martinis, and A. N. Cleland, Phys. Rev. A 86, 032324 (2012).
- [4] C. C. Bultink, T. E. O'Brien, R. Vollmer, N. Muthusubramanian, M. W. Beekman, M. A. Rol, X. Fu, B. Tarasinski, V. Ostroukh, B. Varbanov, A. Bruno, and L. DiCarlo, Science Advances 6, 10.1126/sciadv.aay3050 (2020).
- [5] C. K. Andersen, A. Remm, S. Lazar, S. Krinner, J. Heinsoo, J.-C. Besse, M. Gabureac, A. Wallraff, and C. Eichler, npj Quantum Information 5, 1 (2019).
- [6] C. K. Andersen, A. Remm, S. Lazar, S. Krinner, N. Lacroix, G. J. Norris, M. Gabureac, C. Eichler, and A. Wallraff, Nat. Phys. 16, 875.
- [7] F. W. Strauch, P. R. Johnson, A. J. Dragt, C. J. Lobb, J. R. Anderson, and F. C. Wellstood, Phys. Rev. Lett. 91, 167005 (2003).
- [8] L. DiCarlo, J. M. Chow, J. M. Gambetta, L. S. Bishop, B. R. Johnson, D. I. Schuster, J. Majer, A. Blais, L. Frunzio, S. M. Girvin, and R. J. Schoelkopf, Nature 460, 240

## ACKNOWLEDGMENTS

We thank L. Janssen, M. Rol, M. Sarsby, T. Stavenga, B. Tarasinski, and M. Venkatesh for experimental assistance, C. Eichler and B. Terhal for discussions, and G. Calusine and W. Oliver for providing the travelingwave parametric amplifier used in the readout amplification chain. This research is supported by the Office of the Director of National Intelligence (ODNI), Intelligence Advanced Research Projects Activity (IARPA), via the U.S. Army Research Office Grant No. W911NF-16-1-0071, and by Intel Corporation. The views and conclusions contained herein are those of the authors and should not be interpreted as necessarily representing the official policies or endorsements, either expressed or implied, of the ODNI, IARPA, or the U.S. Government. F. B. is supported by ERC Grant EQEC No. 682726.

(2009).

- [9] S. Sheldon, E. Magesan, J. M. Chow, and J. M. Gambetta, Phys. Rev. A 93, 060302(R) (2016).
- [10] S. S. Hong, A. T. Papageorge, P. Sivarajah, G. Crossman, N. Didier, A. M. Polloreno, E. A. Sete, S. W. Turkowski, M. P. da Silva, and B. R. Johnson, Phys. Rev. A 101, 012302 (2020).
- [11] R. Barends, C. M. Quintana, A. G. Petukhov, Y. Chen, D. Kafri, K. Kechedzhi, R. Collins, O. Naaman, S. Boixo, F. Arute, K. Arya, D. Buell, B. Burkett, Z. Chen, B. Chiaro, A. Dunsworth, B. Foxen, A. Fowler, C. Gidney, M. Giustina, R. Graff, T. Huang, E. Jeffrey, J. Kelly, P. V. Klimov, F. Kostritsa, D. Landhuis, E. Lucero, M. McEwen, A. Megrant, X. Mi, J. Mutus, M. Neeley, C. Neill, E. Ostby, P. Roushan, D. Sank, K. J. Satzinger, A. Vainsencher, T. White, J. Yao, P. Yeh, A. Zalcman, H. Neven, V. N. Smelyanskiy, and J. M. Martinis, Phys. Rev. Lett. 123, 210501 (2019).
- [12] B. M. Varbanov, F. Battistel, B. M. Tarasinski, V. P. Ostroukh, T. E. O'Brien, L. DiCarlo, and B. M. Terhal, npj Quantum Information 6, 102 (2020).
- [13] P. Aliferis and B. M. Terhal, Quantum Info. Comput. 7, 139 (2007).
- [14] J. Ghosh, A. G. Fowler, J. M. Martinis, and M. R. Geller, Phys. Rev. A 88, 062329 (2013).
- [15] A. G. Fowler, Phys. Rev. A 88, 042308 (2013).
- [16] M. Suchara, A. W. Cross, and J. M. Gambetta, Quantum Info. Comput. 15, 997 (2015).
- [17] J. Ghosh and A. G. Fowler, Phys. Rev. A **91**, 020302(R) (2015).
- [18] L. DiCarlo, M. D. Reed, L. Sun, B. R. Johnson, J. M. Chow, J. M. Gambetta, L. Frunzio, S. M. Girvin, M. H. Devoret, and R. J. Schoelkopf, Nature 467, 574 (2010).
- [19] R. Barends, J. Kelly, A. Megrant, A. Veitia, D. Sank, E. Jeffrey, T. C. White, J. Mutus, A. G. Fowler, B. Campbell, Y. Chen, Z. Chen, B. Chiaro, A. Dunsworth, C. Neill, P. O'Malley, P. Roushan, A. Vainsencher, J. Wenner, A. N. Korotkov, A. N. Cleland, and J. M. Martinis, Nature 508, 500 (2014).
- [20] J. Kelly, R. Barends, A. G. Fowler, A. Megrant, E. Jeffrey, T. White, D. Sank, J. Mutus, B. Campbell, Y. Chen,

B. Chiaro, A. Dunsworth, I.-C. Hoi, C. Neill, P. J. J. OMalley, C. Quintana, P. Roushan, A. Vainsencher, A. N. Cleland, J. Wenner, and J. M. Martinis, Nature **519**, 66 (2015).

- [21] J. M. Martinis and M. R. Geller, Phys. Rev. A 90, 022307 (2014).
- [22] S. Krinner, S. Lazar, A. Remm, C. Andersen, N. Lacroix, G. Norris, C. Hellings, M. Gabureac, C. Eichler, and A. Wallraff, Phys. Rev. App. 14, 024042 (2020).
- [23] Y. Chen, C. Neill, P. Roushan, N. Leung, M. Fang, R. Barends, J. Kelly, B. Campbell, Z. Chen, B. Chiaro, A. Dunsworth, E. Jeffrey, A. Megrant, J. Y. Mutus, P. J. J. O'Malley, C. M. Quintana, D. Sank, A. Vainsencher, J. Wenner, T. C. White, M. R. Geller, A. N. Cleland, and J. M. Martinis, Phys. Rev. Lett. 113, 220502 (2014).
- [24] F. Yan, P. Krantz, Y. Sung, M. Kjaergaard, D. L. Campbell, T. P. Orlando, S. Gustavsson, and W. D. Oliver, Phys. Rev. App. 10, 054062 (2018).
- [25] P. Mundada, G. Zhang, T. Hazard, and A. Houck, Phys. Rev. App. **12**, 054023 (2019).
- [26] M. C. Collodo, J. Herrmann, N. Lacroix, C. K. Andersen, A. Remm, S. Lazar, J.-C. Besse, T. Walter, A. Wallraff, and C. Eichler, Phys. Rev. Lett. **125**, 240502 (2020).
- [27] Y. Xu, J. Chu, J. Yuan, J. Qiu, Y. Zhou, L. Zhang, X. Tan, Y. Yu, S. Liu, J. Li, F. Yan, and D. Yu, Phys. Rev. Lett. **125**, 240503 (2020).
- [28] J. A. Schreier, A. A. Houck, J. Koch, D. I. Schuster, B. R. Johnson, J. M. Chow, J. M. Gambetta, J. Majer, L. Frunzio, M. H. Devoret, S. M. Girvin, and R. J. Schoelkopf, Phys. Rev. B 77, 180502(R) (2008).
- [29] M. A. Rol, F. Battistel, F. K. Malinowski, C. C. Bultink, B. M. Tarasinski, R. Vollmer, N. Haider, N. Muthusubramanian, A. Bruno, B. M. Terhal, and L. DiCarlo, Phys. Rev. Lett. **123**, 120502 (2019).
- [30] M. Kjaergaard, M. E. Schwartz, A. Greene, G. O. Samach, M. O. A. Bengtsson, C. M. McNally, J. Braumller, D. K. Kim, P. Krantz, M. Marvian, A. Melville, B. M. Niedzielski, Y. Sung, R. Winik, J. Yoder, D. Rosenberg, S. L. K. Obenland, . T. P. Orlando, I. Marvian, S. Gustavsson, and W. D. Oliver, ArXiv:2001.08838 (2020).
- [31] E. Magesan, J. M. Gambetta, and J. Emerson, Phys. Rev. A 85, 042311 (2012).
- [32] C. J. Wood and J. M. Gambetta, Phys. Rev. A 97, 032306 (2018).
- [33] R. Versluis, S. Poletto, N. Khammassi, B. M. Tarasinski, N. Haider, D. J. Michalak, A. Bruno, K. Bertels, and L. DiCarlo, Phys. Rev. App. 8, 034021 (2017).
- [34] N. Lacroix, C. Hellings, C. K. Andersen, A. Di Paolo, A. Remm, S. Lazar, S. Krinner, G. J. Norris, M. Gabureac, J. Heinsoo, A. Blais, C. Eichler, and A. Wallraff, PRX Quantum 1, 110304 (2020).
- [35] R. Barends, L. Lamata, J. Kelly, L. García-Álvarez, A. Fowler, A. Megrant, E. Jeffrey, T. White, D. Sank, J. Mutus, B. Campbell, Y. Chen, Z. Chen, B. Chiaro, A. Dunsworth, I.-C. Hoi, C. Neill, P. OMalley, C. Quintana, P. Roushan, A. Vainsencher, J. Wenner, E. Solano, and J. Martinis, Nat. Commun. 6, 7654 (2015).
- [36] J. Preskill, Quantum **2**, 79 (2018).
- [37] See Supplemental Material at [URL] for additional information supporting statements and claims made in the main text, which includes Refs. [4, 21, 29, 38, 40, 42–45].

- [38] J. Heinsoo, C. K. Andersen, A. Remm, S. Krinner, T. Walter, Y. Salathé, S. Gasparinetti, J.-C. Besse, A. Potočnik, A. Wallraff, and C. Eichler, Phys. Rev. App. 10, 034040 (2018).
- [39] M. A. Rol, L. Ciorciaro, F. K. Malinowski, B. M. Tarasinski, R. E. Sagastizabal, C. C. Bultink, Y. Salathe, N. Haandbaek, J. Sedivy, and L. DiCarlo, App. Phys. Lett. **116**, 054001 (2020).
- [40] B. Nijholt, J. Weston, J. Hoofwijk, and A. Akhmerov, *Adaptive*: parallel active learning of mathematical functions (2019).
- [41] QuTech Quantum Inspire, https://www.quantuminspire.com/.
- [42] P. Krantz, M. Kjaergaard, F. Yan, T. P. Orlando, S. Gustavsson, and W. D. Oliver, App. Phys. Rev. 6, 021318 (2019).
- [43] C. C. Bultink, B. Tarasinski, N. Haandbaek, S. Poletto, N. Haider, D. J. Michalak, A. Bruno, and L. DiCarlo, App. Phys. Lett. **112**, 092601 (2018).
- [44] F. Motzoi, J. M. Gambetta, P. Rebentrost, and F. K. Wilhelm, Phys. Rev. Lett. 103, 110501 (2009).
- [45] J. M. Chow, L. DiCarlo, J. M. Gambetta, F. Motzoi, L. Frunzio, S. M. Girvin, and R. J. Schoelkopf, Phys. Rev. A 82, 040305 (2010).